



SOPUDAR TECHNOLOGY CO. LTD

Web: www.spd-e.com

Tel: 0086-158 9966 7626 Email: info@spd-e.com

Add: 5F A-B Building, Jinhang Low-Carbon Technology Park, 2th. Lilian Rd,
Tangxia District, Dongguan, Guangdong, China Postal Code: 523710

Rain-proof Power Supply

SR-60W-12



CE FC

Feature:

- 60W Single Output Rain-proof Power Supply
- Output voltage & current: DC12V 5A
- Input voltage range: 180~240VAC
- Built in EMI filter with tiny ripple
- 100% full load burn-in test
- Air Cooling
- Built-in constant current limiting circuit (C.C.+C.V.mode);
- Protection: Short circuit/ Overload/ Over voltage/ Over temperature



Specification:

	Model	SR-60W-12
Output	DC output Voltage	12V±1%
	Output Current Range	0-5A
	Wave and Noise	120mVp-p
	DC output Power	60W
	Efficiency	85%
	DC Voltage Adjustable Scope	(at full load)≤0.5%
Input	Voltage Range	180~240VAC 47-63Hz
	Input Current	0.3A/230V
	Leakage Current	<1mA/ 240VAC
	Inrush Current	Cold start 36A/ 230VAC
Protection	Over-load	105%~135%, Protection type: Constant current limiting, recovers automatically after fault condition is removed
	Over-voltage	105%---150% Rated Voltage, Protection type: Shut off
	High-temperature	RTH3>=65°C FAN ON<=55°C FAN OFF>=80°C Cut off output(5~15V)
Environment	Working temperature & humidity	-10°C~+50°C, 20~90%RH
	Store temperature & humidity	-20°C~+85°C, 10~95%RH
	Temperature coefficient	±0.03%°C(0~50°C)
	Vibration	10~500Hz,2G 10min./1cycle,Period for 60min,EACH AXES
Safety	Withstand voltage	I/P-O/P: 1.5KVAC, I/P-FG: 1.5KVAC, O/P-FG: 0.5KVAC
	Isolation resistance	I/P-O/P,I/P-FG,O/P-FG: 100M Ohms/500VDC
Standard	CE EMC Standard	EN55015:2013+A1:2015, EN61547:2009, EN61000-3-2:2014, EN61000-3-33:2013
	CE LVD Standard	EN61347-2-13:2014+A1:2017, EB61347-1:2015
	ROHS Standard	IEC 62321: 2013, EPA3050B:1996, EN1122:2001, EPA3052:1996, EPA3060A, etc.
Other	Dimension	72*36*118mm (L*W*H)
	Weight	0.23kg
Notes	1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature. 2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor. 3. Tolerance : includes set up tolerance, line regulation and load regulation. 4. I/P-O/P: Input and output interval, I/P-FG: Input and enclosure, O/P-FG: Output and enclosure	



SOPUDAR TECHNOLOGY CO. LTD

Web: www.spd-e.com

Tel: 0086-158 9966 7626 Email: info@spd-e.com

Add: 5F A-B Building, Jinhang Low-Carbon Technology Park, 2th. Lilian Rd,
Tangxia District, Dongguan, Guangdong, China Postal Code: 523710

Rain-proof Power Supply

SR-100W-12



CE FC



Feature:

- 100W Single Output Rain-proof Power Supply
- Output voltage & current: DC12V 8.5A
- Input voltage range: 180~240VAC
- Built in EMI filter with tiny ripple
- 100% full load burn-in test
- Air Cooling
- Built-in constant current limiting circuit (C.C.+C.V.mode);
- Protection: Short circuit/ Overload/ Over voltage/ Over temperature



Specification:

	Model	SR-100W-12
Output	DC output Voltage	12V±1%
	Output Current Range	0-8.5A
	Wave and Noise	120mVp-p
	DC output Power	100W
	Efficiency	85%
	DC Voltage Adjustable Scope	(at full load)≤0.5%
Input	Voltage Range	180~240VAC 47-63Hz
	Input Current	0.45A/230V
	Leakage Current	<1mA/ 240VAC
	Inrush Current	Cold start 36A/ 230VAC
Protection	Over-load	105%~135%, Protection type: Constant current limiting, recovers automatically after fault condition is removed
	Over-voltage	105%---150% Rated Voltage, Protection type: Shut off
	High-temperature	RTH3>=65°C FAN ON<=55°C FAN OFF>=80°C Cut off output(5~15V)
Environment	Working temperature & humidity	-10°C~+50°C, 20~90%RH
	Store temperature & humidity	-20°C~+85°C, 10~95%RH
	Temperature coefficient	±0.03%°C(0~50°C)
	Vibration	10~500Hz,2G 10min./1cycle,Period for 60min,EACH AXES
Safety	Withstand voltage	I/P-O/P: 1.5KVAC, I/P-FG: 1.5KVAC, O/P-FG: 0.5KVAC
	Isolation resistance	I/P-O/P,I/P-FG,O/P-FG: 100M Ohms/500VDC
Standard	CE EMC Standard	EN55015:2013+A1:2015, EN61547:2009, EN61000-3-2:2014, EN61000-3-33:2013
	CE LVD Standard	EN61347-2-13:2014+A1:2017, EB61347-1:2015
	ROHS Standard	IEC 62321: 2013, EPA3050B:1996, EN1122:2001, EPA3052:1996, EPA3060A, etc.
Other	Dimension	72*36*133mm (L*W*H)
	Weight	0.26kg
Notes	1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature. 2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor. 3. Tolerance : includes set up tolerance, line regulation and load regulation. 4. I/P-O/P: Input and output interval, I/P-FG: Input and enclosure, O/P-FG: Output and enclosure	



SOPUDAR TECHNOLOGY CO. LTD

Web: www.spd-e.com

Tel: 0086-158 9966 7626 Email: info@spd-e.com

Add: 5FA-B Building, Jinhang Low-Carbon Technology Park, 2th. Lilian Rd,
Tangxia District, Dongguan, Guangdong, China Postal Code: 523710

Rain-proof Power Supply

SR-200W-12



CE FC

Feature:

- 200W Single Output Rain-proof Power Supply
- Output voltage & current: DC12V 16.7A
- Input voltage range: 180~240VAC
- Built in EMI filter with tiny ripple
- 100% full load burn-in test
- Forced air Cooling by built-in DC fan
- Built-in constant current limiting circuit (C.C.+C.V.mode);
- Protection: Short circuit/ Overload/ Over voltage/ Over temperature



Specification:

	Model	SR-200W-12
Output	DC output Voltage	12V±1%
	Output Current Range	0-16.7A
	Wave and Noise	120mVp-p
	DC output Power	200W
	Efficiency	85%
	DC Voltage Adjustable Scope	(at full load)≤0.5%
Input	Voltage Range	180~240VAC 47-63Hz
	Input Current	0.9A/230V
	Leakage Current	<1mA/ 240VAC
	Inrush Current	Cold start 36A/ 230VAC
Protection	Over-load	105%~135%, Protection type: Constant current limiting, recovers automatically after fault condition is removed
	Over-voltage	105%---150% Rated Voltage, Protection type: Shut off
	High-temperature	RTH3>=65°C FAN ON<=55°C FAN OFF>=80°C Cut off output(5~15V)
Environment	Working temperature & humidity	-10°C~+50°C, 20~90%RH
	Store temperature & humidity	-20°C~+85°C, 10~95%RH
	Temperature coefficient	±0.03%°C(0~50°C)
	Vibration	10~500Hz,2G 10min./1cycle,Period for 60min,EACH AXES
Safety	Withstand voltage	I/P-O/P: 1.5KVAC, I/P-FG: 1.5KVAC, O/P-FG: 0.5KVAC
	Isolation resistance	I/P-O/P,I/P-FG,O/P-FG: 100M Ohms/500VDC
Standard	CE EMC Standard	EN55015:2013+A1:2015, EN61547:2009, EN61000-3-2:2014, EN61000-3-33:2013
	CE LVD Standard	EN61347-2-13:2014+A1:2017, EB61347-1:2015
	ROHS Standard	IEC 62321: 2013, EPA3050B:1996, EN1122:2001, EPA3052:1996, EPA3060A, etc.
Other	Dimension	89*47*126mm (L*W*H)
	Weight	0.38kg
Notes	1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature. 2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor. 3. Tolerance : includes set up tolerance, line regulation and load regulation. 4. I/P-O/P: Input and output interval, I/P-FG: Input and enclosure, O/P-FG: Output and enclosure	



SOPUDAR TECHNOLOGY CO. LTD

Web: www.spd-e.com

Tel: 0086-158 9966 7626 Email: info@spd-e.com

Add: 5F A-B Building, Jinhang Low-Carbon Technology Park, 2th. Lilian Rd,
Tangxia District, Dongguan, Guangdong, China Postal Code: 523710

Rain-proof Power Supply

SR-250W-12



CE FC



Feature:

- 250W Single Output Rain-proof Power Supply
- Output voltage & current: DC12V 21A
- Input voltage range: 180~240VAC
- Built in EMI filter with tiny ripple
- 100% full load burn-in test
- Forced air Cooling by built-in DC fan
- Built-in constant current limiting circuit (C.C.+C.V.mode);
- Protection: Short circuit/ Overload/ Over voltage/ Over temperature



Specification:

	Model	SR-250W-12
Output	DC output Voltage	12V±1%
	Output Current Range	0-21A
	Wave and Noise	120mVp-p
	DC output Power	250W
	Efficiency	85%
	DC Voltage Adjustable Scope	(at full load)≤0.5%
Input	Voltage Range	180~240VAC 47-63Hz
	Input Current	1.2A/230V
	Leakage Current	<1mA/ 240VAC
	Inrush Current	Cold start 36A/ 230VAC
Protection	Over-load	105%~135%, Protection type: Constant current limiting, recovers automatically after fault condition is removed
	Over-voltage	105%---150% Rated Voltage, Protection type: Shut off
	High-temperature	RTH3>=65°C FAN ON<=55°C FAN OFF>=80°C Cut off output(5~15V)
Environment	Working temperature & humidity	-10°C~+50°C, 20~90%RH
	Store temperature & humidity	-20°C~+85°C, 10~95%RH
	Temperature coefficient	±0.03%°C(0~50°C)
	Vibration	10~500Hz,2G 10min./1cycle,Period for 60min,EACH AXES
Safety	Withstand voltage	I/P-O/P: 1.5KVAC, I/P-FG: 1.5KVAC, O/P-FG: 0.5KVAC
	Isolation resistance	I/P-O/P,I/P-FG,O/P-FG: 100M Ohms/500VDC
Standard	CE EMC Standard	EN55015:2013+A1:2015, EN61547:2009, EN61000-3-2:2014, EN61000-3-33:2013
	CE LVD Standard	EN61347-2-13:2014+A1:2017, EB61347-1:2015
	ROHS Standard	IEC 62321: 2013, EPA3050B:1996, EN1122:2001, EPA3052:1996, EPA3060A, etc.
Other	Dimension	89*47*164mm (L*W*H)
	Weight	0.5kg
Notes	1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature. 2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor. 3. Tolerance : includes set up tolerance, line regulation and load regulation. 4. I/P-O/P: Input and output interval, I/P-FG: Input and enclosure, O/P-FG: Output and enclosure	



SOPUDAR TECHNOLOGY CO. LTD

Web: www.spd-e.com

Tel: 0086-158 9966 7626 Email: info@spd-e.com

Add: 5FA-B Building, Jinhang Low-Carbon Technology Park, 2th. Lilian Rd,
Tangxia District, Dongguan, Guangdong, China Postal Code: 523710

Rain-proof Power Supply

SR-400W-12



CE FC

Feature:

- 400W Single Output Rain-proof Power Supply
- Output voltage & current: DC12V 33.3A
- Input voltage range: 180~240VAC
- Built in EMI filter with tiny ripple
- 100% full load burn-in test
- Forced air Cooling by built-in DC fan
- Built-in constant current limiting circuit (C.C.+C.V.mode);
- Protection: Short circuit/ Overload/ Over voltage/ Over temperature



Specification:

	Model	SR-400W-12
Output	DC output Voltage	12V±1%
	Output Current Range	0-33.3A
	Wave and Noise	120mVp-p
	DC output Power	400W
	Efficiency	85%
	DC Voltage Adjustable Scope	(at full load)≤0.5%
Input	Voltage Range	180~240VAC 47-63Hz
	Input Current	1.8A/230V
	Leakage Current	<1mA/ 240VAC
	Inrush Current	Cold start 36A/ 230VAC
Protection	Over-load	105%~135%, Protection type: Constant current limiting, recovers automatically after fault condition is removed
	Over-voltage	105%---150% Rated Voltage, Protection type: Shut off
	High-temperature	RTH3>=65°C FAN ON<=55°C FAN OFF>=80°C Cut off output(5~15V)
Environment	Working temperature & humidity	-10°C~+50°C, 20~90%RH
	Store temperature & humidity	-20°C~+85°C, 10~95%RH
	Temperature coefficient	±0.03%°C(0~50°C)
	Vibration	10~500Hz,2G 10min./1cycle,Period for 60min,EACH AXES
Safety	Withstand voltage	I/P-O/P: 1.5KVAC, I/P-FG: 1.5KVAC, O/P-FG: 0.5KVAC
	Isolation resistance	I/P-O/P,I/P-FG,O/P-FG: 100M Ohms/500VDC
Standard	CE EMC Standard	EN55015:2013+A1:2015, EN61547:2009, EN61000-3-2:2014, EN61000-3-33:2013
	CE LVD Standard	EN61347-2-13:2014+A1:2017, EB61347-1:2015
	ROHS Standard	IEC 62321: 2013, EPA3050B:1996, EN1122:2001, EPA3052:1996, EPA3060A, etc.
Other	Dimension	117*55*165mm (L*W*H)
	Weight	0.55kg
Notes	1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature. 2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor. 3. Tolerance : includes set up tolerance, line regulation and load regulation. 4. I/P-O/P: Input and output interval, I/P-FG: Input and enclosure, O/P-FG: Output and enclosure	